

WEIGHT AND LOADS	
Unladen Trailer Weight (TARE)	660 lbs / 300 Kg
Gross Vehicle Weight Rating (GWVR)	1500 lbs / 680 Kg
LOAD BEARING CAPACITY	
Bottomshell	1000 lbs / 450 Kg
Topshell (i.e. roof rack and people)	500 lbs / 230 Kg
MATTRESSES	
2 x RV Short Queen	60" x 76" ; 1 with 6" foam, 1 with 4" foam 100% polyester, water repellent zipped covers
TENT	
Bedrooms	70" x 80" x 70" roof sloping to 36" at the back
Living Room	9' x 12' x 8' roof sloping to 7.5' on front and sides
Materials	Tent walls and roof: 200 gsm 300D 1500 mm waterproof rating Oxford Ripstop 100% polyester fabric with polyurethane coating For maximum colour fastness yarn is dyed before weaving (solution dyed) Windows: Clear 12 gauge vinyl plastic, noseeum bugnet and fabric layers with YKK zippers Doors: Noseeum bugnet and fabric layer with YKK zippers Ground covering: 16oz Vinyl groundsheet, RV mat and tarp muck sheet Tent poles: Powder coated aluminum
TRAILER	
Topshell	72" x 85" x 12"
Bottomshell	72" x 85" x 13"
Tongue-fitted	2.5" x 2.5" x 48"
Tongue removed	2.5" x 2.5" x 78"
In storage position	4' x 6' x 7.5'
Materials	Shells: Composite (fibreglass) foam sandwich with EPDM seals Rims: 13" 7 spoke aluminum mag rims with 5 on 4.5 bolt pattern Tires and frame: SR175/80R13 C; axle and spring capacity 2000lbs Tongue: powder coated aluminum 4 Stabilizer jacks: 6.5" with 18" travel, each rated for 650lbs Stainless steel hinges and padlock latches Coupler for ball 2" Tongue swivel jack rated for 1000lbs 24" safety chains Lights as required by Transport Canada Plate holder, roof rack tracks
TAILGATE KITCHEN	
Countertop	Main: 48" x 15.5" 2 x side flap extensions: 13" x 12" Total countertop length: 72"
Under counter storage	46" x 15.5" x 10"
Materials	Composite (fibreglass) foam sandwich, Formica countertop, and aluminum legs LED lighting Sealed wood door Trimlok seal Stainless Steel Liftoff hinges Keyed lock